

D03VV-F | Three-core cable




EAN code
D03VV-F 3x0.75/3.2: 8595188165884

| Technical parameters | D03VV-F 3x0.75/3.2 |
|--------------------------------|-------------------------------|
| Rated voltage: | 300 / 300 V |
| Test voltage: | 2 kV |
| Capacity: | max. 12.3 nF / 100 m (328') |
| Core diameter with insulation: | 3.2 mm (0.12") |
| Overall diameter of cable: | 8.1 mm (0.31") |
| Section: | 0.75 mm ² (AWG 18) |
| Length: | 1 m (39.37") |

- Cable to probes SHR-1 and SHR-2, 3x 0.75 mm² (AWG 18) with a certification for drinking water, 1m (39.37").
- Construction:
 - bright copper stranded core of hole
 - core insulation of special PVC
 - sheath of special PVC.
- Technical specifications and usage:
 - the product meets requirements for direct and permanent contact with drinking water according to § 5 of the Act. 258/2000 Decree of the Ministry of Health. 409/2005 Sb., On hygienic requirements for products coming into direct contact with drinking water and water treatment
 - usable up to 70 °C (158 °F)
 - suitable for submersible conductivity probes for the boreholes, wells and tanks
 - suitable for probes used for level detection of conductive liquids.
 - cable capacity is max. 12.3 nF / 100 m (328')

Cross-section



D05V-K | Power cable



EAN code
D05V-K 0.75/3.2: 8595188165945

| Technical parameters | D05V-K 0.75/3.2 |
|--------------------------------|-------------------------------|
| Rated voltage: | 300 / 500 V |
| Test voltage: | 2 kV |
| Capacity: | max. 12.3 nF / 100 m (328') |
| Core diameter with insulation: | 3.2 mm (0.12") |
| Section: | 0.75 mm ² (AWG 18) |
| Length: | 1 m (39.37") |

- Cable to probes SHR-1 and SHR-2, 3x 0.75 mm² (AWG 18) with a certification for drinking water, 1m (39.37").
- Construction:
 - bright copper stranded core of hole
 - insulation of special PVC.
- Technical specifications and usage:
 - the product meets requirements for direct and permanent contact with drinking water according to § 5 of the Act. 258/2000 Decree of the Ministry of Health. 409/2005 Sb., On hygienic requirements for products coming into direct contact with drinking water and water treatment
 - usable up to 70 °C (158 °F)
 - suitable for probes used for level detection of conductive liquids.